SAFETY DATA SHEET



Veet Hair Removal Kit - Sensitive Skin - Hair Removal Cream

1. Product and company identification

: Veet Hair Removal Kit - Sensitive Skin - Hair Removal Cream **Product name**

Distributed by : Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9

CANADA

: 1-800-338-6167

Telephone: +1 905 283 7000

Emergency telephone

number (Medical)

Emergency telephone

number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: : http://www.rbnainfo.com

Product use : To remove unwanted body hair.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of **USDOL** Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS# : D8229061 v5.0

Formulation #: : Veet Hair Removal Base Cream - Normal, Skynet Cha59VEMAS; TDS #8185517

Veet Hair Removal Base Cream - Dry, Skynet Cha59VEMCR; TDS #8185523 Veet Hair Removal Base Cream - Sensitive, Skynet Cha59VEMDS; TDS #8185435 Veet Hair Removal Base Cream - Suprem'Essence, Skynet Cha59VEM8R; TDS

#8185518

: ABL tubes, PBL tubes, pump packs - 50ml, 100ml, 200ml, 400ml **UPC Code / Sizes**

Code # : D8229061 v5.0 **Date of issue** : 18/10/2016 1/13

2. Hazards identification

Classification of the substance or mixture : SERIOUS EYE DAMAGE - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 2%

GHS label elements

Hazard pictograms



Signal word : Danger

: Causes serious eye damage. **Hazard statements**

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

Prevention : Wear eye or face protection.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER or

physician.

Storage : Not applicable. **Disposal** : Not applicable.

Supplemental label

elements

: If ingested, seek medical advice immediately and show the container or the label.

Hazards not otherwise

classified

: None known.

3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|---------------------------------------|---|--|
| thioglycolic acid calcium dihydroxide | 5 - 10 2.5 - 5 2.5 - 5 2.5 - 5 | 57-13-6 68-11-1 1305-62-0 1310-58-3 |
| Alcohols, C16-18, ethoxylated | 1 - 2.5 | 68439-49-6 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

FF8185517_FF8185523_FF8185435_FF8185518 SDS # Code # : D8229061 v5.0 **Date of issue** : 18/10/2016 2/13

4. First aid measures

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

4. First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

nitrogen oxides sulfur oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

FF8185517_FF8185523_FF8185435_FF8185518 SDS # : D8229061 v5.0 Code # **Date of issue** : 18/10/2016 4/13 (D8229061) US

6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Exposure limits

ALLIA MEEL (Limited Ctetes 40/2044)

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name

| urea | AIHA WEEL (United States, 10/2011). TWA: 10 mg/m³ 8 hours. |
|------|--|
| | ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 1 ppm 8 hours. TWA: 3.8 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 1 ppm 8 hours. TWA: 4 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 1 ppm 10 hours. TWA: 4 mg/m³ 10 hours. |
| | ACGIH TLV (United States, 4/2014). TWA: 5 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 5 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). |

Code # : D8229061 v5.0 **Date of issue** : 18/10/2016 5/13 (D8229061) US

8. Exposure controls/personal protection

TWA: 5 mg/m³ 8 hours. Form: Respirable

fraction

TWA: 15 mg/m³ 8 hours. Form: Total dust

ACGIH TLV (United States, 4/2014).

C: 2 mg/m³

OSHA PEL 1989 (United States, 3/1989).

CEIL: 2 mg/m³

NIOSH REL (United States, 10/2013).

TWA: 2 mg/m³ 10 hours.

Appropriate engineering controls

potassium hydroxide

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

9. Physical and chemical properties

Appearance

Physical state : Liquid. [Viscous]

Color : White.

Odor : Characteristic. : Not available. **Odor threshold**

Ha : 12.4 to 12.6 [Conc. (% w/w): 100%]

Melting point : Not available. **Boiling point** : Not available.

Flash point : Closed cup: >93.3°C (>199.9°F)

Evaporation rate : Not available. : Not available. Flammability (solid, gas) Lower and upper explosive : Not available.

(flammable) limits

: Not available. Vapor pressure Vapor density : Not available. **Relative density** : 1.04 to 1.1

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available.

: Dynamic (room temperature): 70000 to 130000 mPa·s (70000 to 130000 cP) **Viscosity**

Flow time (ISO 2431) : Not available.

10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

Conditions to avoid

: No specific data.

Incompatible materials : Do not use with other products.

Reactive or incompatible with the following materials:

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

FF8185517_FF8185523_FF8185435_FF8185518 SDS # Code # : D8229061 v5.0 **Date of issue** : 18/10/2016 7/13

11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------------|-----------------------|---------|------------|----------|
| urea | LD50 Oral | Rat | 8471 mg/kg | - |
| thioglycolic acid | LC50 Inhalation Vapor | Rat | 210 mg/m³ | 4 hours |
| | LD50 Oral | Rat | 114 mg/kg | - |
| calcium dihydroxide | LD50 Oral | Rat | 7340 mg/kg | - |
| potassium hydroxide | LD50 Oral | Rat | 273 mg/kg | - |
| Alcohols, C16-18, ethoxylated | LD50 Oral | Rat | 1260 mg/kg | - |
| | LDLo Dermal | Rabbit | 1260 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|----------------------------------|--------------------------|------------|-------|---|-------------|
| urea | Skin - Mild irritant | Human | - | 72 hours 22 milligrams Intermittent | - |
| | Skin - Moderate irritant | Human | - | 24 hours 20 Percent | - |
| calcium dihydroxide | Eyes - Severe irritant | Rabbit | - | 10 milligrams | - |
| potassium hydroxide | Eyes - Moderate irritant | Rabbit | - | 24 hours 1 milligrams | - |
| | Skin - Severe irritant | Guinea pig | - | 24 hours 50 milligrams | - |
| | Skin - Severe irritant | Human | - | 24 hours 50 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 50 milligrams | - |
| Alcohols, C16-18, ethoxylated | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 microliters | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 microliters | - |
| *Veet Hair Removal Base Cream | Skin - Edema | Human | 0 | - | - |

Conclusion/Summary

Skin

: Non-irritant to skin. * Information is based on toxicity test result of the product.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

FF8185517_FF8185523_FF8185435_FF8185518 SDS # : D8229061 v5.0 **Date of issue** : 18/10/2016 Code # 8/13

11. Toxicological information

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Code # : FF8185517_FF8185523_FF8185518 SDS # : D8229061 v5.0 Date of issue : 18/10/2016 9/13

11. Toxicological information

| Route | ATE value |
|-------|--------------|
| Oral | 2117.6 mg/kg |

12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-------------------------------------|--|----------|
| urea | Acute EC50 6573.1 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute EC50 3910000 μg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 5000 µg/l Fresh water | Fish - Colisa fasciata - Fingerling | 96 hours |
| | Chronic NOEC 2 g/L Fresh water | Fish - Heteropneustes fossilis | 30 days |
| thioglycolic acid | Acute LC50 30000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| calcium dihydroxide | Acute LC50 33884.4 μg/l Fresh water | Fish - Clarias gariepinus - Fingerling | 96 hours |
| potassium hydroxide | Acute LC50 80 ppm Fresh water | Fish - Gambusia affinis - Adult | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| urea | <-1.73 | - | low |
| thioglycolic acid | -2.99 | | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Release of large quantities into water may cause a pH-change resulting in danger for aquatic life.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues.

Code # : FF8185517_FF8185523_FF8185435_FF8185518 SDS # : D8229061 v5.0 Date of issue : 18/10/2016 10/13

13. Disposal considerations

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

Not a DOT controlled material (United States). Not a TDG-controlled material. This preparation is not classified as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA).

15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

> United States inventory (TSCA 8b): Not determined. Clean Water Act (CWA) 311: potassium hydroxide

Clean Air Act Section 112 : Listed

(b) Hazardous Air **Pollutants (HAPs)**

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602 : Not listed

Class II Substances

DEA List I Chemicals : Not listed

(Precursor Chemicals)

DEA List II Chemicals : Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

: Not applicable. **SARA 304 RQ**

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|-------------------------------|---------|-------------|----------------------------------|----------|--|--|
| urea | 5 - 10 | No. | No. | No. | Yes. | No. |
| thioglycolic acid | 2.5 - 5 | No. | No. | No. | Yes. | No. |
| calcium dihydroxide | 2.5 - 5 | No. | No. | No. | Yes. | No. |
| potassium hydroxide | 2.5 - 5 | No. | No. | No. | Yes. | No. |
| Alcohols, C16-18, ethoxylated | 1 - 2.5 | No. | No. | No. | Yes. | No. |

State regulations

Massachusetts : The following components are listed: POTASSIUM HYDROXIDE; THIOGLYCOLIC

ACID; SOAPSTONE; CALCIUM HYDROXIDE; GLYCERINE MIST

New York : The following components are listed: Potassium hydroxide

: D8229061 v5.0 Date of issue 11/13 Code # : 18/10/2016

15. Regulatory information

New Jersey

: The following components are listed: POTASSIUM HYDROXIDE; CAUSTIC POTASH; THIOGLYCOLIC ACID; ACETIC ACID, MERCAPTO-; MINERAL OIL (UNTREATED and MILDLY TREATED); SOAPSTONE; CALCIUM HYDROXIDE; HYDRATED LIME; GLYCERIN; 1,2,3-PROPANETRIOL; TITANIUM DIOXIDE; TITANIUM OXIDE (TiO2)

Pennsylvania

: The following components are listed: POTASSIUM HYDROXIDE (K(OH)); ACETIC ACID, MERCAPTO-; SOAPSTONE DUST; CALCIUM HYDROXIDE (CA(OH)2); 1,2, 3-PROPANETRIOL; TITANIUM OXIDE (TIO2)

Canada

WHMIS (Canada)

: Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

Class E: Corrosive material

Canadian lists

Canadian NPRI

: The following components are listed: White mineral oil

CEPA Toxic substances

: None of the components are listed.

Canada inventory

: Not determined.

Label elements

Precautionary measures


: For external use only

If ingested, seek medical advice immediately and show the container or the label.

Avoid contact with eyes. Keep out of reach of children.

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

FF8185517_FF8185523_FF8185435_FF8185518 SDS # Code # : D8229061 v5.0 **Date of issue** : 18/10/2016 12/13

16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Date of issue : 18/10/2016

Date of previous issue : No previous validation

Version : 5

Prepared by : Reckitt Benckiser Hull (UK)

Dansom Lane Hull, HU8 7DS United Kingdom T +44 (0)1482 326151 F +44 (0)1482 582532

Revision comments: Updated transport section

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.