SAFETY DATA SHEET



SCALPICIN Maximum Strength Anti-Itch Liquid

1. Product and company identification

Product name SCALPICIN Maximum Strength Anti-Itch Liquid

Distributed by : Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Emergency telephone number (Medical)

: 1-800-338-6167

Emergency telephone number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: http://www.rbnainfo.com

Product use : Skin protection

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS # : D0344854 v2.0 **Formulation** #: : RD4760 v2.0

2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 2

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements: Highly flammable liquid and vapor.

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 1/13

2. Hazards identification

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosionproof electrical, ventilating, lighting and all material-handling equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Keep container tightly closed.

Response

: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage

: Store in a well-ventilated place. Keep cool.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: None known.

Hazards not otherwise

: None known.

classified

3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Ethyl alcohol	30 - 60	64-17-5
hydrocortisone	1 - 2.5	50-23-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Code # : RD4760 (D0344854) SDS# : D0344854 v2.0 **Date of issue** : 09/04/2015. 2/13

4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: May cause eye irritation upon direct contact with eyes.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

: Do not use water jet.

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer

may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray

to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 3/13

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible. absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Code # : RD4760 (D0344854) SDS# : D0344854 v2.0 **Date of issue** : 09/04/2015. 4/13

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name	Exposure limits
Ethyl alcohol	ACGIH TLV (United States, 6/2013).
•	STEL: 1000 ppm 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 1000 ppm 10 hours.
	TWA: 1900 mg/m ³ 10 hours.
	OSHA PEL (United States, 2/2013).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m ³ 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 5/13

8. Exposure controls/personal protection

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. Physical and chemical properties

Appearance

Physical state : Liquid. Color : Colorless.

Odor : Alcohol-like. : Not available. **Odor threshold** pН : Not available. : Not available. **Melting point Boiling point** : Not available.

Flash point : Closed cup: 21°C (69.8°F)

Evaporation rate : Not available. Flammability (solid, gas) Not available. Lower and upper explosive

(flammable) limits

Vapor pressure

: Not available.

: Not available. Vapor density : Not available. **Relative density** : 0.9 to 0.97

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available. **Viscosity** : Not available.

10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur. reactions

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

: Reactive or incompatible with the following materials: Incompatible materials

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Code # : RD4760 (D0344854) SDS# : D0344854 v2.0 **Date of issue** : 09/04/2015. 6/13

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
hydrocortisone	LD50 Oral	Rat	5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl alcohol	Eyes - Moderate irritant	Rabbit	-	0.06666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
hydrocortisone	Skin - Moderate irritant	Woman	-	1 Percent	-
*SCALPICIN MAX.+ HYDROCORTISONE	Eyes - Cornea opacity	Rabbit	<1	72 hours	4 days

Conclusion/Summary

Eyes

: Moderately irritating to eyes. * Information is based on toxicity test result of the concentrate of a similar product.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 7/13

11. Toxicological information

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact : May cause eye irritation upon direct contact with eyes.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	481927.9 mg/kg

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 8/13

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 µg/l Fresh water Acute LC50 25500 µg/l Marine water Acute LC50 42000 µg/l Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss	96 hours 48 hours 48 hours
	Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	96 hours 12 weeks

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethyl alcohol	-0.35	-	low
hydrocortisone	1.61	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 9/13

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	NA1993	Compounds, cleaning liquid (ethanol)	3	II	NAME TO SERVICE STATE OF THE S	Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions IB2, T7, TP1, TP8, TP28
TDG Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (ethanol)	3	II	&	Explosive Limit and Limited Quantity Index 1 Passenger Carrying Road or Rail Index 5 Special provisions 16
Mexico Classification	UN1993	LIQUIDO INFLAMABLE, N.E.P. (ethanol)	3	II	<u>*</u>	Special provisions 274
IMDG Class	UN1993	FLAMMABLE LIQUID, N.O.S. (ethanol)	3	II	&	Emergency schedules (EmS) F-E, _S-E_ Special provisions 274
IATA-DGR Class	UN1993	Flammable liquid, n.o. s. (ethanol)	3	II		Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 353 Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 364 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions:

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 10/13

Conforms to USDOL OSHA 29CFR 1910.1200 HAZCOM

D0344854 v2.0 14. Transport information Y341 Special provisions А3

PG* : Packing group

15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**

: Not listed

Clean Air Act Section 602

: Not listed

Class I Substances

: Not listed

Clean Air Act Section 602 **Class II Substances**

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard Composition/information on ingredients

Name	 hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Ethyl alcohol hydrocortisone	Yes. No.		No. No.	Yes. Yes.	No. No.

State regulations

Massachusetts : The following components are listed: ETHYL ALCOHOL

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL; PROPYLENE

GLYCOL; 1,2-PROPANEDIOL

: The following components are listed: DENATURED ALCOHOL; 1,2-PROPANEDIOL **Pennsylvania**

Label elements

Precautionary measures : Read label before use.

Avoid contact with eyes.

: D0344854 v2.0 **Date of issue** : 09/04/2015. Code # : RD4760 (D0344854) SDS# 11/13

15. Regulatory information

Keep out of reach of children.

Do not ingest.


Hazard statements



Flammable

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships.

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 12/13

16. Other information

Date of issue : 09/04/2015.

Date of previous issue : 28/06/2011

Version : 2

Prepared by : Reckitt Benckiser LLC.

Product Safety Department

1 Philips Parkway

Montvale, New Jersey 07646-1810 USA.

FAX: 201-476-7770

Revision comments : Revision as per US GHS

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.

Code # : RD4760 (D0344854) SDS # : D0344854 v2.0 Date of issue : 09/04/2015. 13/13