SAFETY DATA SHEET



BRASSO® Metal Polish (Canada)

1. Product and company identification

Product name : BRASSO® Metal Polish (Canada)

Distributed by : Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9

CANADA

: 1-800-338-6167

Telephone: +1 905 283 7000

Emergency telephone

number (Medical)

Emergency telephone : 1-800

number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: : http://www.rbnainfo.com

Product use : Metal cleaning.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS # : D8049596 v5.0 **Formulation** #: : #8043677 v1.0

UPC Code / Sizes : 62338-00117-06 (Noxon Metal Polish 12oz), 26600-89331-00 (Brasso Metal Polish 8oz),

56200-81382-01 (Brasso Metal Polish 142ml)

Code # : FF8043677 SDS # : D8049596 v5.0 Date of issue : 25/05/2018 1/14

2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2B

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : Flammable liquid and vapor. Causes eye irritation.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container

tightly closed. Wash hands thoroughly after handling.

Response : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical attention.

Storage : Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Supplemental label

elements

: None known.

Hazards not otherwise

classified

: None known.

3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|-------------------|--------|------------|
| Pumice | 3 - 7 | 1332-09-8 |
| Isopropyl alcohol | 1 - 5 | 67-63-0 |
| Ammonia solution | 5 - 10 | 1336-21-6 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Code # : FF8043677 SDS # : D8049596 v5.0 Date of issue : 25/05/2018 2/14

4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower evelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. If irritation persists, get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

> not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire,

symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

: Flush contaminated skin with plenty of water. Remove contaminated clothing and Skin contact

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eve contact : Causes eve irritation.

Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> irritation watering redness

Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Code # : FF8043677 SDS# : D8049596 v5.0 **Date of issue** : 25/05/2018 3/14

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

metal oxide/oxides

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact

Code # : FF8043677 SDS# : D8049596 v5.0 **Date of issue** : 25/05/2018 4/14

6. Accidental release measures

information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Control

Occupational exposure limits

| Ingredient name | Exposure limits |
|-------------------|--|
| Isopropyl alcohol | ACGIH TLV (United States, 3/2015). |
| | TWA: 200 ppm 8 hours. |
| | STEL: 400 ppm 15 minutes. |
| | OSHA PEL 1989 (United States, 3/1989). |
| | TWA: 400 ppm 8 hours. |
| | TWA: 980 mg/m³ 8 hours. |
| | STEL: 500 ppm 15 minutes. |
| | STEL: 1225 mg/m³ 15 minutes. |
| | NIOSH REL (United States, 10/2013). |
| | TWA: 400 ppm 10 hours. |
| | TWA: 980 mg/m³ 10 hours. |
| | STEL: 500 ppm 15 minutes. |
| | STEL: 1225 mg/m³ 15 minutes. |
| | OSHA PEL (United States, 2/2013). |
| | TWA: 400 ppm 8 hours. |
| | TWA: 980 mg/m³ 8 hours. |
| | |

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code # : FF8043677 SDS# : D8049596 v5.0 **Date of issue** : 25/05/2018 5/14

8. Exposure controls/personal protection

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Safety eyewear complying with an approved standard should be used when a risk Eye/face protection

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless

the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be

> worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

Personal protective equipment for the body should be selected based on the task being **Body protection**

> performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing

should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

: Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

9. Physical and chemical properties

Appearance

Physical state : Liquid. [Viscous liquid.]

Color : Opaque. Light tan.

Odor : Ammoniacal.

: Not available. **Odor threshold**

pН **Melting point** : Not available.

Boiling point : Not available.

Flash point : Closed cup: 40.56 to 43.33°C (105 to 110°F)

9.6 to 10.2

Evaporation rate : Not available. Flammability (solid, gas) : Not available.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : Not available. Vapor density : Not available. : 1.104 to 1.14 Relative density

Code # : FF8043677 SDS# : D8049596 v5.0 **Date of issue** : 25/05/2018 6/14

9. Physical and chemical properties

Solubility
Partition coefficient: n-

octanol/water

Not available.

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): 8000 to 11000 mPa·s (8000 to 11000 cP)

Flow time (ISO 2431) : Not available.

10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidizing materials

: The product is stable.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-------------|---------|-------------|----------|
| Isopropyl alcohol | LD50 Dermal | | 12800 mg/kg | - |
| | LD50 Oral | Rat | 5000 mg/kg | - |
| Ammonia solution | LD50 Oral | Rat | 350 mg/kg | - |

Conclusion/Summary: Based on available data, the classification criteria are not met.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------|-------------|
| Isopropyl alcohol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 10 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |
| Ammonia solution | Eyes - Severe irritant | Rabbit | - | 250 Micrograms | - |
| | Eyes - Severe irritant | Rabbit | - | 0.5 minutes 1 milligrams | - |

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Causes eye irritation.

Respiratory: Based on available data, the classification criteria are not met.

Sensitization

11. Toxicological information

Not available.

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity
Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Isopropyl alcohol | - | 3 | - |

Reproductive toxicity

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|-------------------|------------|-------------------|------------------|
| Isopropyl alcohol | Category 3 | Not applicable. | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Code # : FF8043677 SDS # : D8049596 v5.0 Date of issue : 25/05/2018 8/14

11. Toxicological information

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|---------------|
| Oral | 12927.7 mg/kg |

12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|---------------------------------|----------|
| Isopropyl alcohol | Acute LC50 1400000 µg/l Marine water | Crustaceans - Crangon crangon | 48 hours |
| | Acute LC50 4200 mg/l Fresh water | Fish - Rasbora heteromorpha | 96 hours |
| Ammonia solution | Acute LC50 37 ppm Fresh water | Fish - Gambusia affinis - Adult | 96 hours |

Conclusion/Summary: Based on available data, the classification criteria are not met.

Persistence and degradability

Code # : FF8043677 SDS # : D8049596 v5.0 Date of issue : 25/05/2018 9/14

12. Ecological information

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Isopropyl alcohol | 0.05 | - | low |

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|--------------------------|-----------|---|---------|-----|------------|------------------------|
| DOT Classification | UN1987 | Alcohols, n.o.s. | 3 | III | \Diamond | Limited quantity |
| TDG Classification | UN1987 | ALCOHOLS, N.O.S. (Isopropyl alcohol) | 3 | III | \Diamond | Limited quantity |
| Mexico Classification | UN1987 | ALCOHOLES, N.E.P. (Isopropyl alcohol) | 3 | III | \Diamond | Limited quantity |
| IMDG Class | UN1987 | ALCOHOLS, N.O.S. (Isopropyl alcohol) | 3 | III | \Diamond | Limited quantity |
| | | | | | | |

14. Transport information IATA-DGR Class UN1987 Alcohols, n.o.s. (Isopropyl alcohol) 3 III See DG List

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

PG*: Packing group

15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 311: ammonia

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Due source of Chemicals)

: Not listed

(Precursor Chemicals)

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard

Immediate (acute) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|-------------------|---------|----------------|----------------------------------|----------|--|--|
| Isopropyl alcohol | 1 - 2.5 | Yes. | No. | No. | Yes. | No. |
| Ammonia solution | 1 - 2.5 | No. | No. | No. | Yes. | No. |

SARA 313

Code # : FF8043677 SDS # : D8049596 v5.0 Date of issue : 25/05/2018 11/14

15. Regulatory information

| | Product name | CAS number | % |
|---------------------------------|---------------|----------------------|-----------------|
| Form R - Reporting requirements | 1.000.000.000 | 67-63-0 1336-21-6 | 2.178 1.9248 |
| Supplier notification | 1.000,000 | 67-63-0 1336-21-6 | 2.178 1.9248 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: CALCIUM CARBONATE; ISOPROPYL ALCOHOL;

2-PROPANOL; AMMONIUM HYDROXIDE

New York : The following components are listed: Ammonium hydroxide

New Jersey : The following components are listed: CALCIUM CARBONATE; LIMESTONE;

ISOPROPYL ALCOHOL; 2-PROPANOL; AMMONIUM HYDROXIDE

Pennsylvania : The following components are listed: LIMESTONE; ETHANEDIOIC ACID, DIHYDRATE;

ISOPROPYL ALCOHOL MANUFACTURE (STRONG-ACID PROCESS); AMMONIUM

HYDROXIDE ((NH4)(OH))

Canada

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C

(200°F).

Class D-2A: Material causing other toxic effects (Very toxic).

Class E: Corrosive material

Canadian lists

Canadian NPRI : The following components are listed: Isopropyl alcohol; Ammonia (total)

CEPA Toxic substances : None of the components are listed.Canada inventory : All components are listed or exempted.

Label elements

Signal word : CAUTION

Hazard statements: EYE AND SKIN IRRITANT.


Precautionary measures : Keep out of the reach of children. DO NOT get in eyes or on skin.

Wash hands immediately after use. DO NOT treat garments while wearing.

Additional information: Contains Ammonia.

16. Other information

Hazardous Material Information System (U.S.A.)



16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Date of issue : 25/05/2018 Date of previous issue : 09/06/2016.

Version : 5

Prepared by : Reckitt Benckiser India Ltd

Plot No 48 Sector - 32 Institutional Area Gurgaon, Haryana India - 122001

Revision comments : Section 3 range update

Indicates information that has changed from previously issued version.

Notice to reader

16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.