SAFETY DATA SHEET

LYSOL® Disinfectant Spray - Brand New Day™ - Mango & Hibiscus



1. Product and company identification

Product name	: LYSOL® Disinfectant Spray - Brand New Day™ - Mango & Hibiscus
Distributed by	 Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600 Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9 CANADA Telephone: +1 905 283 7000
Emergency telephone number (Medical)	: 1-800-338-6167
Emergency telephone number (Transport)	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887
Website:	: http://www.rbnainfo.com

Product use

: Disinfectant. Consumer use

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS #	:	D8277741
Formulation #	:	FF8274004 (Mango & Hibiscus)
EPA #	:	777-99

ŝ

2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 2 GASES UNDER PRESSURE - Compressed gas EYE IRRITATION - Category 2B

GHS label elements Hazard pictograms



Code # : FF8274004_D8277741 SDS # (NA)

: D8277741

2. Hazards identification

Signal word	: Warning
Hazard statements	: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation.
Precautionary statements	
General	: Not applicable.
Prevention	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
Response	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F.
Disposal	: Not applicable.
Supplemental label elements	: None known.
Hazards not otherwise classified	: None known.

3. Composition/information on ingredients

Substance/mixture : Mixture		
Ingredient name	%	CAS number
Ethanol (Ethyl Alcohol)	30 - 60	64-17-5
Butane	5 - 10	106-97-8
propane	1 - 5	74-98-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. First aid measures

Description of necessary first aid measures			
Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.	
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.	

D8277	741
-------	-----

4. First aid mea	sures
Ingestion Most important symptor	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Potential acute health e	entects
Eye contact	: Causes eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	<u>ymptoms</u>

<u></u>		
Eye contact	: Adverse symptoms may include the following: irritation watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	: No specific data.	
Ingestion	: No specific data.	

Indication of immediate mee	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	<u>ont</u>	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

<u>Control</u>

Occupational exposure limits

Ingredient name	Exposure limits
ethanol	ACGIH TLV (United States, 1/2022).
	STEL: 1000 ppm 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2020).
	TWA: 1000 ppm 10 hours.
	TWA: 1900 mg/m ³ 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m³ 8 hours.
butane	OSHA PEL 1989 (United States, 3/1989).
	TWA: 800 ppm 8 hours.
	TWA: 1900 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2020).
	TWA: 800 ppm 10 hours.
	TWA: 1900 mg/m ³ 10 hours.
	ACGIH TLV (United States, 1/2022).
	[Butane] Explosive potential.
	STEL: 1000 ppm 15 minutes.
propane	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1800 mg/m ³ 8 hours.
	TWA: 1000 ppm 8 hours.
	NIOSH REL (United States, 10/2020).
	TWA: 1000 ppm 10 hours.
	TWA: 1800 mg/m ³ 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 1000 ppm 8 hours.
	TWA: 1800 mg/m ³ 8 hours.
	ACGIH TLV (United States, 1/2022). Oxyger
ode # : FF8274004_D8277741 SDS # : D8277741 (NA)	Date of issue : 12/11/2023 5/14

8. Exposure controls/personal protection

	Depletion [Asphyxiant]. Exp	losive potential.
Appropriate engineering controls	Juse only with adequate ventilation. If user operations generate dust, for or mist, use process enclosures, local exhaust ventilation or other engino o keep worker exposure to airborne contaminants below any recommo imits. The engineering controls also need to keep gas, vapor or dust o below any lower explosive limits. Use explosion-proof ventilation equip	neering controls ended or statutory concentrations
Environmental exposure controls	Emissions from ventilation or work process equipment should be check hey comply with the requirements of environmental protection legislati cases, fume scrubbers, filters or engineering modifications to the proce will be necessary to reduce emissions to acceptable levels.	on. In some
Individual protection measu		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical pro- eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contamin Wash contaminated clothing before reusing. Ensure that eyewash sta showers are close to the workstation location.	eriod. ated clothing.
Eye/face protection	Safety eyewear complying with an approved standard should be used vassessment indicates this is necessary to avoid exposure to liquid splagases or dusts. If contact is possible, the following protection should be assessment indicates a higher degree of protection: chemical spla	ishes, mists, e worn, unless
Skin protection		0.00
Hand protection	Chemical-resistant, impervious gloves complying with an approved sta worn at all times when handling chemical products if a risk assessmen necessary. Considering the parameters specified by the glove manufa during use that the gloves are still retaining their protective properties. noted that the time to breakthrough for any glove material may be diffe glove manufacturers. In the case of mixtures, consisting of several sul protection time of the gloves cannot be accurately estimated.	t indicates this is icturer, check It should be rent for different
Body protection	Personal protective equipment for the body should be selected based operformed and the risks involved and should be approved by a special nandling this product. When there is a risk of ignition from static electristatic protective clothing. For the greatest protection from static dischashould include anti-static overalls, boots and gloves.	ist before icity, wear anti-
Other skin protection	Appropriate footwear and any additional skin protection measures sho based on the task being performed and the risks involved and should b specialist before handling this product.	
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that appropriate standard or certification. Respirators must be used accord respiratory protection program to ensure proper fitting, training, and othe aspects of use.	ling to a

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearar	<u>nce</u>			
Physica	l state	: Liquid. [Liquefi	ed compressed gas	.]
Color		: Clear.		
Odor		: Not available.		
Odor thre	shold	: Not available.		
Code #	: FF8274004_ (NA)	D8277741	: D8277741	Date of issu

Section 9. Physical and chemical properties and safety characteristics

рН	:	10.5	i to 11.8 [Conc. (% w/w): 100%]		
Melting point/freezing point	: Not available.				
Boiling point, initial boiling point, and boiling range	:	Not available.			
Flash point	:	Clos	Closed cup: 25.6°C (78.1°F)		
Evaporation rate	:	Not	available.		
Flammability	:	Not	available.		
Lower and upper explosion limit/flammability limit	:	Not	available.		
Vapor pressure	:	Not	available.		
Relative vapor density	:	Not	available.		
Relative density	:	: Not available.			
Solubility(ies)	:				
Media			Result		
cold water hot water			Easily soluble Easily soluble		
Solubility in water	:	: Not available.			
Partition coefficient: n- octanol/water	:	Not	applicable.		
Auto-ignition temperature	: Not available.		available.		
Decomposition temperature	1	Not	available.		
Heat of combustion	1	: 17.56 kJ/g			
Viscosity	:	: Not available.			
Particle characteristics					
Median particle size	: Not applicable.				
<u>Aerosol product</u>					
Type of aerosol	1	: Spray			
Ignition distance	:	<45	.72 cm		

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

7/14

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Lysol Brand III Kills 99.9% of Viruses & Bacteria ** Disinfectant Max Cover Mist (Brand New Day (Bali Breeze)_Tropic Thunder_FF8274004 (D8277741)	LC50 Inhalation Vapor	Rat	>2.75 mg/l	4 hours
Ethanol (Ethyl Alcohol) Butane	LD50 Dermal LD50 Oral LC50 Inhalation Vapor LD50 Oral LC50 Inhalation Vapor	Rabbit Rat Rat Rat Rat	>5050 mg/kg >5050 mg/kg 124700 mg/m ³ 7 g/kg 658000 mg/m ³	- - 4 hours - 4 hours

Conclusion/Summary : Not classified. Bridging principle "Substantially similar mixtures"

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Lysol Brand III Kills 99.9% of Viruses & Bacteria ** Disinfectant Max Cover Mist (Brand New Day (Bali Breeze)_Tropic Thunder_FF8274004 (D8277741)	Eyes - Mild irritant	Rabbit	-	72 hours	4 days
	Skin - Mild irritant	Rabbit	-	4 hours	72 hours
Ethanol (Ethyl Alcohol)	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 uL	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-

Conclusion/Summary

Skin

Eyes

: Slightly irritating to the skin. Bridging principle "Substantially similar mixtures"

: Mildly irritating to the eyes. Bridging principle "Substantially similar mixtures"

Respiratory

: Based on available data, the classification criteria are not met.

Sensitization

Not available.

Conclusion/Summary Skin : Based on available data, the classification criteria are not met. Respiratory : Based on available data, the classification criteria are not met. **Mutagenicity** Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

: FF8274004 D8277741 SDS # Code # (NA)

: D8277741

11. Toxicological information

Carcinogenicity

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethanol (Ethyl Alcohol)	-	1	-

Reproductive toxicity

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effect	<u>s</u>	
Evo contact	÷ .	Causes eve irritatio

Eye contact	Causes eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also ch	nronic effects from sh	<u>ort and long term exposure</u>
Short term exposure		
Potential immediate : Not availab effects	ble.	
Code # : FF8274004_D8277741 SDS # (NA)	: D8277741	Date of issue : 12/11/2023

11. Toxicological information

: Not available.
: Not available.
: Not available.
ects
: Based on available data, the classification criteria are not met.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		Dermal (mg/kg)		(vapors)	Inhalation (dusts and mists) (mg/ I)
(7000	N/A	N/A	124.7	N/A
	N/A	N/A	N/A	658	N/A

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethanol (Ethyl Alcohol)	Acute EC50 3306 mg/l Marine water Acute EC50 1074 mg/l Fresh water Acute LC50 5680 mg/l Fresh water Acute LC50 11000000 µg/l Marine water Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa Crustaceans - Cypris subglobosa Daphnia - Daphnia magna - Neonate Fish - Alburnus alburnus Algae - Ulva pertusa	96 hours 48 hours 48 hours 96 hours 96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethanol (Ethyl Alcohol)	-0.35	-	low
Butane	2.89	-	low
propane	1.09	-	low

12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN1950	UN1950	UN1950	UN1950
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
2.1	2.1	2.1	2.1
-	-	-	-
No.	No.	No.	No.
	UN1950 Aerosols 2.1 -	UN1950 Aerosols 2.1 - - UN1950 AEROSOLS 2.1 - -	UN1950 UN1950 UN1950 Aerosols AEROSOLS AEROSOLS 2.1

- **DOT Classification** : Limited quantity
- **TDG Classification** : Limited quantity
 - : Limited quantity
 - : See DG list

IMDG

ΙΑΤΑ

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

15. Regulatory information

U.S. Federal regulations	:
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

SARA 302/304

Composition/information on ingredients

			SARA 302 1	PQ	SARA 304 F	Q
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ammonia	Proprietary	Yes.	500	-	100	-

SARA 304 RQ

: 343642.6 lbs / 156013.7 kg

SARA 311/312

Classification

: FLAMMABLE AEROSOLS - Category 2 GASES UNDER PRESSURE - Compressed gas EYE IRRITATION - Category 2B

Composition/information on ingredients

Name	%	Classification
Ethanol (Ethyl Alcohol)	30 - 60	FLAMMABLE LIQUIDS - Category 2
		EYE IRRITATION - Category 2A
Butane	5 - 10	FLAMMABLE GASES - Category 1
		GASES UNDER PRESSURE - Compressed gas
propane	1 - 5	FLAMMABLE GASES - Category 1
		GASES UNDER PRESSURE - Compressed gas

State regulations Massachusetts

New York

New Jersey

:	The following components are liste	ed: Ethanol (Ethyl Al	cohol); Butane; PROPANE

: None of the components are listed.

- : The following components are listed: Ethanol (Ethyl Alcohol); Butane; PROPANE
- Pennsylvania
- : The following components are listed: Ethanol (Ethyl Alcohol); Butane; PROPANE

California Prop. 65

A This product does not require a Safe Harbor warning under California Prop. 65.

Label elements

<u>CPSC</u>

Signal word : CAUTION

Hazard statements : CONTENTS UNDER PRESSURE. FLAMMABLE AEROSOLS Causes moderate eye irritation.

Code #	:FF8274004_D8277741 SDS #	: D8277741	Date of issue : 12/11/2023	12/14
	(NA)			


15. Regulatory information

Precautionary measures	: Keep out of the reach of children. Keep away from heat, sparks and flame. Do not puncture or incinerate container. Do not spray in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.
<u>CCCR</u>	
Signal word Hazard statements	: PRECAUTIONS : CONTENTS UNDER PRESSURE AND MAY CATCH FIRE.
Precautionary measures	: KEEP OUT OF REACH OF CHILDREN. DO NOT use in presence of open flame or spark. DO NOT smoke or burn, puncture or incinerate container or store at temperatures over 50°C. DO NOT place in hot water or near radiators, stoves or other sources of heat. Avoid contact with eyes and food. Use only in well ventilated areas. Store away from heat. For surfaces and/or objects that may come into direct contact with food or children at the mouthing stage of development, a rinse with potable water is recommended.

Additional information / Recommendations

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



NFPA (30B) aerosol Flammability Level I

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
Date of issue	: 12/11/2023
Date of previous issue	: 12/12/2023
Version	: 4.0
Prepared by	: Reckitt Benckiser India Ltd Plot No 48 Sector - 32 Institutional Area Gurgaon, Haryana India - 122001

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.