SAFETY DATA SHEET

HEALTH + HYGIENE + HOME

EASY-OFF® Oven Cleaner - Fume Free Max Aerosol - Lemon

1. Product and company identification				
Product name	: EASY-OFF® Oven Cleaner - Fume Free Max Aerosol - Lemon			
Distributed by	: Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9 CANADA Telephone: +1 905 283 7000			
	Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600			
Emergency telephone number (Medical)	: 1-800-338-6167			
Emergency telephone number (Transport)	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887			
Website:	: http://www.rbnainfo.com			
Product use	: Oven Cleaner			

Consumer use This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS #	÷	D8362661v3.0
Formulation #	:	3101813 v1.0

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Oven Cleaner	
Consumer use	

2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE AEROSOLS - Category 2 GASES UNDER PRESSURE - Liquefied gas EYE IRRITATION - Category 2A
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.
Precautionary statements	
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
Response	: IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
Storage	: Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Disposal	: Not applicable.
Supplemental label elements	: None known.
Hazards not otherwise classified	: None known.

3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
1-(1-methyl-2-propoxyethoxy)propan-2-ol	≥5 - ≤10	29911-27-1
Isobutane	≥3 - ≤7	75-28-5
potassium carbonate	≤3-≤7	584-08-7
2-aminoethanol	≤1-≤5	141-43-5
benzyl alcohol	<0.5-<1.5	100-51-6
d-Limonene	<1	5989-27-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

: D8362661v3.0

4. First aid measures

Description of necessary f	rst aid measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

most important symptoms/	incolo, doute and delayed
Potential acute health effe	<u>ets</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate mee	dical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Code #	: 3101813_D8362661	SDS #	: D8362661v3.0	Date of issue	: 01/29/2020	3/15
	(NA)					

4. First aid measures

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code #	: 3101813_D8362661	SDS #	: D8362661v3.0	Date of issue	: 01/29/2020	4/15
	(NA)					

6. Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
-------------	--

7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Conditions for safe storage, including any	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area.

incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name	Exposure limits	
Isobutane	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2018). STEL: 1000 ppm 15 minutes.	
2-aminoethanol	ACGIH TLV (United States, 3/2018). TWA: 3 ppm 8 hours. TWA: 7.5 mg/m ³ 8 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m ³ 15 minutes. OSHA PEL 1989 (United States, 3/1989) TWA: 3 ppm 8 hours. TWA: 8 mg/m ³ 8 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 3 ppm 10 hours. TWA: 8 mg/m ³ 10 hours. STEL: 6 ppm 15 minutes. STEL: 6 ppm 15 minutes. STEL: 15 mg/m ³ 15 minutes.).
l Code # : 3101813_D8362661 SDS # (NA)	I	/15

	OSHA PEL (United States, 5/2018).				
	TWA: 6 mg/m ³ 8 hours.				
benzyl alcohol	AIHA WEEL (United States, 5/2018). TWA: 10 ppm 8 hours.				
d-Limonene	AIHA WEEL (United States, 5/2018). TWA: 30 ppm 8 hours.				
Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, va or mist, use process enclosures, local exhaust ventilation or other engineering cont to keep worker exposure to airborne contaminants below any recommended or stat limits. The engineering controls also need to keep gas, vapor or dust concentration below any lower explosive limits. Use explosion-proof ventilation equipment.	rols tutor ns			
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.				
Individual protection measured					
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.				
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unler the assessment indicates a higher degree of protection: chemical splash goggles.	SS			
Skin protection					
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates th necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differ glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	iis is k rent			
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.				
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved specialist before handling this product.				
Respiratory protection	 Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. 				

9. Physical and chemical properties

Appearance

Physical state	: Liquid. [Liquefied compressed gas.]	
Color	: White.	
Odor	: Lemon-like.	
Odor threshold	: Not available.	
рН	: 12.5 [Conc. (% w/w): 100%][25°C]	
Melting point	: Not available.	
Boiling point	: Not available.	
Flash point	: Open cup: >93.3°C (>199.9°F) [Concentration]	
Evaporation rate	: Not available.	
Flammability (solid, gas)	: Not available.	
Lower and upper explosive (flammable) limits	: Not available.	
Vapor pressure	: Not available.	
Vapor density	: Not available.	
Relative density	: Not available	
Solubility	: Not available.	
Partition coefficient: n- octanol/water	: Not available.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
Viscosity	: Not available.	
Aerosol product		
Type of aerosol	: Foam	
Heat of combustion	: 2.615 kJ/g	
Flame height	: <45 cm	

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: Do not mix with household chemicals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

7/15

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isobutane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
potassium carbonate	LD50 Oral	Rat	1870 mg/kg	-
2-aminoethanol	LD50 Oral	Rat	1720 mg/kg	-
benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-
-	LD50 Oral	Rat	1230 mg/kg	-
d-Limonene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	4400 mg/kg	-
Easy-Off® FF Max Oven	LD50 Oral	Rat	>5000 mg/kg	-
Cleaner Aerosol - Lemon				
scent_D8362661_NA				

Conclusion/Summary : Not classified. Harmful* Information is based on toxicity test result of a similar product.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-aminoethanol	Eyes - Severe irritant	Rabbit	-	250 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	505 milligrams	-
benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16 milligrams	-
	Skin - Moderate irritant	Pig	-	100 Percent	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
d-Limonene	Skin - Mild irritant	Rabbit	-	24 hours 10 Percent	-
Easy-Off® FF Max Oven Cleaner Aerosol - Lemon scent D8362661 NA	Eyes - Edema of the conjunctivae	Rabbit	>2	-	14 days
	Skin - Erythema/Eschar	Rabbit	0.59	-	-

Conclusion/Summary

Skin

: Non-irritant to skin.

: Moderate irrritant to eyes.

* Information is based on toxicity test result of a similar product.

* Information is based on toxicity test result of a similar product.

Eyes

(NA)

Respiratory

y : Based on available data, the classification criteria are not met.

```
Sensitization
```

Not available.

Conclusion/Summary					
Skin	: Based on ava	ilable data, the classifi	cation criteria are	not met.	
Respiratory	: Based on available data, the classification criteria are not met.				
Mutagenicity					
Not available.					
Conclusion/Summary	: Based on ava	ilable data, the classifi	cation criteria are	not met.	
Carcinogenicity					
Not available.					
Code # : 3101813_D8362	2661 SDS #	: D8362661v3.0	Date of issue	: 01/29/2020	

11. Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Classification

Product/ingredient name	OSHA	IARC	NTP
d-Limonene	-	3	-

Reproductive toxicity

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
d-Limonene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effec	<u>ts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph Eye contact	 Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	No aposifia data
	: No specific data.

Delayed and immediate eff	ects and also chronic effects from short and long term exposure	
Short term exposure		
Potential immediate effects	: Not available.	

Code #	: 3101813_D8362661	SDS #	: D8362661v3.0	Date of issue : 01/29/2020	9/15
	(NA)				

11. Toxicological information

Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	 Based on available

Conclusion/Summary	Based c	n available data, the classification criteria are not met.
General	No know	vn significant effects or critical hazards.
Carcinogenicity	No know	vn significant effects or critical hazards.
Mutagenicity	No know	vn significant effects or critical hazards.
Teratogenicity	No know	vn significant effects or critical hazards.
Developmental effects	No know	vn significant effects or critical hazards.
Fertility effects	No know	vn significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Isobutane	N/A	N/A	N/A	658	N/A
potassium carbonate	1870	N/A	N/A	N/A	N/A
2-aminoethanol	1720	N/A	N/A	N/A	N/A
benzyl alcohol	1230	2000	N/A	N/A	N/A
d-Limonene	4400	N/A	N/A	N/A	N/A

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
potassium carbonate	Acute LC50 630 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 650 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
2-aminoethanol	Acute EC50 8.42 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Acute LC50 >100000 μg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 170 mg/l Fresh water	Fish - Carassius auratus	96 hours
benzyl alcohol	Acute LC50 10000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
d-Limonene	Acute EC50 421 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 688 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12. Ecological information

Persistence and degradability

Conclusion/Summary

: The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1-(1-methyl-2-propoxyethoxy) propan-2-ol	0.88	-	low
Isobutane	2.8	-	low
2-aminoethanol	-1.31	-	low
benzyl alcohol	0.87	-	low
d-Limonene	4.38	-	high

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

	TDG Classification	DOT Classification	IMDG	ΙΑΤΑ
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	Aerosols	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1	2.1
Packing group	111			
Code # : 3101 (NA)	813_D8362661 SDS #	: D8362661v3.0	Date of issue : 01/2	29/2020 11/15

14. Transport information

Environmental hazards	No.		No.	No.	No.
Additional informa	ation				
DOT Classificatio	on	Quantity	<u>uantity</u> No. <u>g instruction</u> Exceptions: <u>limitation</u> Passenger airc <u>rovisions</u> N82		
TDG Classificatio	on	Goods Re <u>Explosive</u>	assified as per the followir gulations: 2.13-2.17 (Clas <u>E Limit and Limited Quar</u> Fr Carrying Road or Rail	s 2). <u>ntity Index</u> 1	oortation of Dangerous
IMDG			cy schedules F-D, S-U rovisions 63, 190, 277, 3	27, 959, 344	
ΙΑΤΑ		Cargo Airo Passenge	limitation Passenger and craft Only: 150 kg. Packag r Aircraft: 30 kg. Packagin <u>rovisions</u> A145, A167, A8	ing instructions: 203. Li g instructions: Y203.	ackaging instructions: 203. mited Quantities -
Special precaution	s for user	upright an	t within user's premises d secure. Ensure that pers n accident or spillage.		ed containers that are oduct know what to do in the
Transport in bulk a to Annex II of MAR		: Not availa	ble.		

the IBC Code

15. Regulatory information

• •	
U.S. Federal regulations	 TSCA 8(a) PAIR: 1,1'-oxydipropan-2-ol TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): All components are listed or exempted. Clean Air Act (CAA) 112 regulated flammable substances: Isobutane
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.
Code # : 3101813_D8362 (NA)	2661 SDS # : D8362661v3.0 Date of issue : 01/29/2020 12/15

15. Regulatory information

SARA 311/312

Classification

: FLAMMABLE AEROSOLS - Category 2 GASES UNDER PRESSURE - Liquefied gas EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
Isobutane	≥3 - ≤7	FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas
potassium carbonate	≤3-≤7	ACUTE TOXICITY (oral) - Category 4
2-aminoethanol	≤1-≤5	FLAMMABLE LIQUIDS - Category 4
		ACUTE TOXICITY (oral) - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
benzyl alcohol	<0.1-<1	ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (dermal) - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
d-Limonene	<1	FLAMMABLE LIQUIDS - Category 3
		SKIN IRRITATION - Category 2
		SKIN SENSITIZATION - Category 1B
		ASPIRATION HAZARD - Category 1

State regulations

Massachusetts	 The following components are listed: ISOBUTANE; ETHANOLAMINE; 2-AMINOETHANOL
New York	: None of the components are listed.
New Jersey	 The following components are listed: Isobutane; PROPANE, 2-METHYL-; ETHANOLAMINE; ETHANOL, 2-AMINO-
Pennsylvania <u>California Prop. 65</u>	: The following components are listed: PROPANE, 2-METHYL-; ETHANOL, 2-AMINO-

This product does not require a Safe Harbor warning under California Prop. 65.

<u>Label elements</u> <u>CPSC</u>	
Signal word	: CAUTION
Hazard statements	: EYE IRRITANT CONTENTS UNDER PRESSURE.
Precautionary measures	: Keep out of the reach of children.DO NOT get in eyes. Wash hands after application and removal. DO NOT puncture or incinerate container. DO NOT expose to heat or store at temperatures above 120°F (49°C).
CCCR	
Signal word	: CAUTION
Hazard statements	: Eye Irritant: CONTENTS UNDER PRESSURE
	CONTAINER MAY EXPLODE IF HEATED
Precautionary measures	: Keep out of the reach of children. DO NOT get in eyes. DO NOT breathe fumes.DO NOT puncture or burn. DO NOT expose to heat or store at temperatures above 49°C.

Additional information / Recommendations

Code #	: 3101813_D8362661	SDS #	: D8362661v3.0	Date of issue	: 01/29/2020	13/15
	(NA)					

15. Regulatory information

Additional information

: If in eyes, IMMEDIATELY rinse eyes with water, remove any contact lenses and continue rinsing eyes for at least 15 minutes. If irritation persists, get medical attention. If swallowed, DO NOT induce vomiting, call a Poison Control Centre or physician immediately.

For US Only:

Contains no phosphorus. Contains Monoethanolamine and Dipropylene Glycol n-Propyl Ether

For Canada Only:

Contains Dipropylene Glycol n-Propyl Ether, Isobutane and Monoethanolamine.

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



NFPA (30B) aerosol Flammability Level 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 197	Key to abbreviations	IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient
---	----------------------	---

Code #	: 3101813_D8362661	SDS #	: D8362661v3.0	Date of issue :	01/29/2020	14/15
	(NA)					

16. Other information

	UN = United Nations
Date of issue	: 01/29/2020
Date of previous issue	: 07/03/2019
Version	: 3.0
Prepared by	: Reckitt Benckiser India Ltd Plot No 48 Sector - 32 Institutional Area Gurgaon, Haryana India - 122001

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.