

# Safety Data Sheet

Revision Date: 05/25/2021

## Section 1: Product and Company Identification

| Product Name:<br>Chemical Family:   | Biofreeze Professional Gel Colorless (846S)<br>Mixture          |  |
|---|---|--|
| Recommended Use:<br>Restrictions on Use:  | Topical Pain Reliever<br>No Data                                |  |
| Company:  | Performance Health, Inc.<br>1245 Home Avenue<br>Akron, OH 44310 |  |
| Telephone:  | (330) 633-8460 (Only available during normal business hours.)   |  |
| Email:  | web@biofreeze.com   |  |
| Emergency Telephone:<br>CHEMTREC (Transport<br>U.S. Coast Guard Natio<br>Response Center: | ation): (800) 424-9300  |  |

#### Section 2: Hazards Identification

Emergency Overview: Warning: Flammable. May cause eye irritation.

### GHS Classification:

Flammable Liquid, Category 3 Eye Irritant, Category 2B

### **GHS Label Elements:**

Pictograms:



Signal Word: Warning

#### Hazard Statements:

H226: Flammable liquid and vapor H320: Causes eye irritation

#### **Precautionary Statements:**

P210: Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

P233: Keep container tightly closed.

P264: Wash hands thoroughly after handling.

P403 + P235: Store in a well-ventilated place. Keep cool.

#### Classification According to Directive 1999/45/EC:

**European Economic Community Information:** This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

EU Classification: [R10] Flammable, [Xi] Irritant

EU Risk Phrases: R10: Flammable; R36: Irritating to eyes.

**EU Safety Phrases:** S2: Keep out of reach of children; S7: Keep container tightly closed; S16: Keep away from sources of ignition – No smoking; S25: Avoid contact with eyes; S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

EU Symbols:



#### Section 3: Composition/Information on Ingredients

| Chemical<br>Ingredients: | CAS<br>Number: | EC<br>Number | Index Number  | Percent<br>Range: | Classification<br>of Ingredient<br>according to<br>67/548/EEC* | Classification<br>of Ingredient<br>according to<br>Regulation<br>(EC) No<br>1272/2008<br>[CLP]* |
|--------------------------|----------------|--------------|---------------|-------------------|--|---|
| Isopropyl<br>Alcohol     | 67-63-0        | 200-661-7    | 603-117-00-0  | 15 - 40%          | F; R11<br>Xi; R36<br>R67                                       | Flam. Liq. 2<br>H225<br>Eye Irrit. 2<br>H319<br>STOT Single 3<br>H336                           |
| L-Menthol                | 2216-51-5      | 218-690-9    | Not Available | 3 – 7%            | Not classified. S<br>community work<br>lim                     | place exposure  |
| Triethanolamine          | 102-71-6       | 203-049-8    | Not Available | 1 – 3%            | Xi; R36/37/38<br>R36   | Eye Irrit. 2<br>H319  |

\*Legend: F: Highly flammable R11: Highly flammable Xi: Irritant R36: Irritating to eyes R67: Vapors may cause drowsiness or dizziness H225: Highly flammable liquid and vapor H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

#### Section 4: First Aid Measures

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if victim feels unwell.

Skin Contact: Not applicable.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### Section 5: Fire Fighting Measures

Suitable Extinguishing Media: Water, carbon dioxide, dry chemical, or foam

Specific Hazards in Case of Fire: None known.

**Special Protective Equipment for Fire-Fighters:** Use protective clothing and breathing equipment appropriate for the surrounding fire.

#### Section 6: Accidental Release Measures

**Personal Precautions:** Eliminate all ignition sources and heat sources if safe to do so. Take off contaminated clothing and wash before reuse.

Environmental Precautions: Do not flush into surface water or sanitary sewer system.

**Methods for Containment/Cleaning Up:** Contain spillage and collect with non-combustible absorbent material. Disposal should be in accordance with all applicable local, state and federal regulations.

#### Section 7: Handling and Storage

**Handling:** Avoid breathing vapor or mist. Wash hands thoroughly after handling. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Keep out of reach of children.

**Storage:** Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

#### Section 8: Exposure Controls/Personal Protection

# US Exposure Limits:

| Chemical<br>Ingredients: | CAS<br>Number: | OSHA PEL            | NIOSH REL  | ACGIH TLV                       |
|--------------------------|----------------|---------------------|--|---------------------------------|
| Isopropyl Alcohol        | 67-63-0        | 400 ppm             | 400 ppm (TWA)<br>500 ppm (STEL)<br>2000 ppm (IDLH) | 200 ppm (TWA)<br>400 ppm (STEL) |
| L-Menthol                | 2216-51-5      | Not<br>Established  | Not Established                                    | Not Established                 |
| Triethanolamine          | 102-71-6       | 5 mg/m <sup>3</sup> | Not Established                                    | 5 mg/m³                         |

# Other Exposure Limits:

| Isopror | oyl Alcohol:    |   |
|---------|-----------------|---|
| looplor | China:          | 700 mg/m <sup>3</sup> STEL; 350 mg/m <sup>3</sup> TWA                       |
|         | Hong Kong:      | 500 ppm STEL; 1230 mg/m <sup>3</sup> STEL;                                  |
|         | riong riong.    | 400 ppm TWA; 983 mg/m <sup>3</sup> TWA                                      |
|         | Indonesia:      | 500 ppm STEL; 1230 mg/m <sup>3</sup> STEL;                                  |
|         |                 | 400 ppm TWA; 983 mg/m <sup>3</sup> TWA                                      |
|         | Japan:          | 200 ppm Administrative Control Level (ACL)                                  |
|         | • P             | 400 ppm Ceiling; 980 mg/m <sup>3</sup> Ceiling                              |
|         | Korea:          | 400 ppm STEL; 980 mg/m <sup>3</sup> STEL;                                   |
|         | i torou.        | 200 ppm TWA; 480 mg/m <sup>3</sup> TWA                                      |
|         | Malaysia:       | 400 ppm TWA; 980 mg/m <sup>3</sup> TWA                                      |
|         | Philippines:    | 400 ppm TWA; 980 mg/m <sup>3</sup> TWA                                      |
|         | Singapore:      | 500 ppm STEL; 1230 mg/m <sup>3</sup> STEL;                                  |
|         | enigapere.      | 400 ppm TWA; 983 mg/m <sup>3</sup> TWA                                      |
|         | Taiwan:         | 500 ppm STEL; 1228.75 mg/m <sup>3</sup> STEL;                               |
|         | raiwan.         | 400 ppm TWA; 983 mg/m <sup>3</sup> TWA                                      |
|         | Russia:         | 50 mg/m <sup>3</sup> STEL (vapor); 10 mg/m <sup>3</sup> TWA (vapor)         |
|         | Austria:        | 800 ppm STEL; 2000 mg/m <sup>3</sup> STEL (4 x 15 min)                      |
|         |                 | 800 ppm STEL; 2000 mg/m <sup>3</sup> STEL (4 x 30 min)                      |
|         |                 | 200 ppm MAK; 500 mg/m <sup>3</sup> MAK;                                     |
|         | Belgium:        | 400 ppm STEL; 1000 mg/m <sup>3</sup> STEL;                                  |
|         |                 | 200 ppm TWA; 500 mg/m <sup>3</sup> TWA                                      |
|         | Bulgaria:       | 1225.0 mg/m <sup>3</sup> STEL; 980.0 mg/m <sup>3</sup> TWA                  |
|         | Czech Republic: |   |
|         | Denmark:        | 200 ppm TWA; 490 mg/m <sup>3</sup> TWA                                      |
|         | Estonia:        | 250 ppm STEL; 600 mg/m <sup>3</sup> STEL;                                   |
|         |                 | 150 ppm TWA; 350 mg/m <sup>3</sup> TWA                                      |
|         | Finland:        | 250 ppm STEL; 620 mg/m <sup>3</sup> STEL;                                   |
|         |                 | 200 ppm TWA; 500 mg/m <sup>3</sup> TWA                                      |
|         | France:         | 400 ppm TWA; 980 mg/m <sup>3</sup> STEL                                     |
|         | Germany:        | 400 ppm Peak; 1000 mg/m <sup>3</sup> Peak;                                  |
|         | •               | 200 ppm MAK; 500 mg/m <sup>3</sup> MAK                                      |
|         | Greece:         | 500 ppm STEL; 1225 mg/m <sup>3</sup> STEL;                                  |
|         |                 | 400 ppm TWA; 980 mg/m <sup>3</sup> TWA                                      |
|         | Hungary:        | 2000 mg/m <sup>3</sup> STEL; 500 mg/m <sup>3</sup> TWA                      |
|         | Ireland:        | 400 ppm STEL; 200 ppm TWA   |
|         | Italy:          | 400 ppm STEL; 200 ppm TWA   |
|         | Latvia:         | 600 mg/m <sup>3</sup> STEL; 350 mg/m <sup>3</sup> TWA                       |
|         | Lithuania:      | 250 ppm STEL; 600 mg/m <sup>3</sup> STEL;                                   |
|         |                 | 150 ppm TWA; 350 mg/m³ TWA  |
|         | Netherlands:    | 10000 mg/m <sup>3</sup> Life Threatening Value (LBW); 200 mg/m <sup>3</sup> |
|         |                 | Prescribed Target Value (VRW); 2000 mg/m <sup>3</sup> Warning Limit         |
|         |                 | Value (AGW)   |
|         |                 |   |

|          | Poland:<br>Portugal:<br>Romania:                | 1200 mg/m <sup>3</sup> STEL; 900 mg/m <sup>3</sup> TWA<br>400 ppm STEL; 200 ppm TWA<br>203 ppm STEL; 500 mg/m <sup>3</sup> STEL;<br>81 ppm TWA; 200 mg/m <sup>3</sup> TWA |  |  |  |
|----------|---|---|--|--|--|
|          | Slovakia:                                       | 1000 mg/m <sup>3</sup> Ceiling; 200 ppm TWA; 500 mg/m <sup>3</sup> TWA  |  |  |  |
|          | Slovenia:                                       | 800 ppm STEL; 2000 mg/m <sup>3</sup> STEL;<br>200 ppm TWA; 500 mg/m <sup>3</sup> TWA  |  |  |  |
|          | Spain:  | 500 ppm STEL; 1250 mg/m <sup>3</sup> STEL;<br>400 ppm TWA; 998 mg/m <sup>3</sup> TWA  |  |  |  |
|          | Sweden:   | 250 ppm STEL; 600 mg/m <sup>3</sup> STEL;   |  |  |  |
|          | United Kingdom:                                 | 150 ppm TLV; 350 mg/m³ TLV<br>500 ppm STEL; 1250 mg/m³ STEL;<br>400 ppm TWA; 999 mg/m³ TWA  |  |  |  |
| L-Ment   | hol:  |   |  |  |  |
|          | Russia:   | 1 mg/m <sup>3</sup> (aerosol and vapor)   |  |  |  |
| Triethar | Triethanolamine:                                |   |  |  |  |
|          | Netherlands:<br>Ireland:<br>Russia:<br>Sweeden: | 5 mg/m <sup>3</sup> TWA<br>5 mg/m <sup>3</sup> TWA<br>5 mg/m <sup>3</sup> TWA<br>5 mg/m <sup>3</sup> TWA; 10 mg/m <sup>3</sup> STEL                                       |  |  |  |

Engineering Controls: Use only in a well-ventilated area.

#### **Personal Protective Equipment:**

Eye Protection: None required under normal conditions of use.

Hand Protection: Not Applicable

Skin and Body Protection: Not Applicable

Respiratory Protection: None required under normal conditions of use.

Hygiene Measures: Wash hands thoroughly after handling. Use only in a well-ventilated area.

#### **Section 9: Physical and Chemical Properties**

| Physical State:            | Gel             |
|----------------------------|-----------------|
| Color:                     | Colorless       |
| Odor:                      | Menthol Scented |
| Odor Threshold:            | Not Available   |
| pH:                        | 6.0 - 7.0       |
| Melting/Freezing Point:    | Not Available   |
| Initial Boiling Point:     | Not Available   |
| Flash Point:               | ≥73.4°F (≥23°C) |
| Evaporation Rate:          | Not Available   |
| Flammability (solid, gas): | Not Applicable  |
| Lower Explosive Limit:     | Not Available   |

| Upper Explosive Limit:            | Not Available |
|-----------------------------------|---------------|
| Lower Flammability Limit:         | 20%           |
| Upper Flammability Limit:         | 35%           |
| Vapor Pressure:                   | Not Available |
| Vapor Density:                    | Not Available |
| Relative Density:                 | 0.95 ± 0.05   |
| Water Solubility:                 | Complete      |
| Partition Coefficient:            | Not Available |
| Autoignition Temperature:         | Not Available |
| <b>Decomposition Temperature:</b> | Not Available |
| Viscosity:                        | Not Available |

#### Section 10: Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Sources of ignition, heat, sunlight, pressure.

Incompatible Materials: Strong acids and oxidizers.

Hazardous Decomposition Products: Alcoholic vapors.

Hazardous Polymerization: Will not occur.

#### Section 11: Toxicological Information

Inhalation: No known effects.

Ingestion: May be harmful if swallowed.

Skin Contact: Relieves pain when used in accordance with instructions.

Eye Contact: May cause eye irritation.

Chronic Exposure: No known effects.

Aggravation of Pre-existing Conditions: No information found.

Numerical Measures of Toxicity: None available.

Carcinogenicity: Not known to be as defined by OSHA, IARC or NTP.

#### Section 12: Ecological Information

This product is safe for the environment at the concentrations predicted under normal use conditions.

#### Section 13: Disposal Considerations

Dispose of contents/container in accordance with all applicable local, state and national regulations.

#### Section 14: Transport Information

| <b>US DOT:</b><br>Proper shipping name:<br>Hazard class:<br>UN Number:<br>Packing Group:<br>Labels: | Flammable liquid nos (contains isopropyl alcohol)<br>3 Flammable liquid<br>UN 1993<br>III<br>Flammable Liquid Class 3 |
|---|---|
| If a Limited Quantity (49CFR 173.   | .150) then ship as follows:   |
| Proper shipping name:   | Not required.   |
| Hazard class:<br>UN Number:   | Not required.   |
| Labels:   | Not required.<br>Use ground limited quantity label.   |
|   |   |
| DOT Hazardous Substance RQ:   | None/no reportable quantities   |
| DOT Marine Pollutants:  | None/no reportable quantities   |
| ΙΑΤΑ:   |   |
| Proper shipping name:   | Flammable liquid nos (contains isopropyl alcohol)   |
| Hazard class:   | 3 Flammable liquid  |
| UN Number:  | UN 1993<br>III  |
| Packing Group:<br>Labels:   | Flammable Liquid, Air limited quantity Y label.   |
| 2400101   |   |
| If a Limited Quantity (49CFR 17   |   |
| Proper shipping name:<br>Hazard Class:  | Flammable liquid nos (contains isopropyl alcohol)   |
| UN Number:  | 3 (Flammable)<br>UN1993   |
| Packing Group:  |   |
| Labels:   | Air limited quantity Y label.   |
| IMDG (All domestic and internation  | al shinments by Ocean)  |
| Proper shipping name:   | Flammable liquid nos (contains isopropyl alcohol)   |
| Hazard Class:   | 3 (Flammable)   |
| UN Number:  | UN1993  |
| Packing Group:<br>Labels:   | <br>Flommable Liquid  |
| Lapeis.   | Flammable Liquid  |
|   |   |

#### *If a Limited Quantity (49CFR 173.150) then ship as follows:*

| Proper shipping name: | Flammable liquid nos(contains isopropyl alcohol), LTD. QTY. |
|-----------------------|---|
| Hazard Class:         | 3 (Flammable)   |
| UN Number:            | UN1993  |
| Packing Group:        | III   |
| Labels:               | Limited Quantity  |
|                       |   |

### Section 15: Regulatory Information

# US Regulatory Information:

#### **OSHA Hazards:** Flammable, Irritant

SARA 302: None/no reportable quantities.

SARA 311/312 Hazard Categories: Fire Hazard, Acute Health Hazard

**SARA 313:** Isopropyl Alcohol (CAS #67-63-0) is subject to SARA 313 reporting requirements.

**TSCA:** All substances in this product are listed on the TSCA inventory if required.

#### Canadian Regulatory Information:

**DSL List:** All components of this product comply with registration requirements.

**European Economic Community Information for Constituents:** The following information is available for the components of this product:

Isopropyl Alcohol: EU EINECS/ELINCS Number: 200-661-7 Glycerin: EU EINECS/ELINCS Number: 200-289-5

L-Menthol: EU EINECS/ELINCS Number: 218-690-9

**EU Labeling and Classification According to Directive 1999/45/EC:** This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

EU Classification: [R10] Flammable, [Xi] Irritant

**EU Risk Phrases:** R10: Flammable; R36: Irritating to eyes; R67: Vapors may cause drowsiness or dizziness.

**EU Safety Phrases:** S2: Keep out of reach of children; S7: Keep container tightly closed; S16: Keep away from sources of ignition – No smoking; S25: Avoid contact with eyes; S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Japanese Information:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I Specified Chemical Substances or Class II Specified Chemical Substances by the Japanese MITI.

**Japanese ENCS Inventory:** The components of this product are on the ENCS Inventory if required.

**Poisonous and Deleterious Substances Control Law:** No component of this product is a listed poisonous, deleterious, or specified poisonous substance under the Poisonous and Deleterious Substances Control Law.

#### **Other International Chemical Inventories:**

China Inventory of Existing Chemical Substances (IECSC): The components of this product are on the IECSC if required.

**Korean Existing Chemicals List (KECL):** The components of this product are on the KECL if required.

**Philippines Inventory of Chemicals and Chemical Substances (PICCS):** The components of this product are on the PICCS if required.

#### Section 16: Other Information

The information contained in this MSDS is presented in good faith and believed to be accurate based on the information provided. The MSDS does not purport to be all inclusive, and shall be used only as a guide. While Performance Health, Inc. believes that the data contained herein comply with 29 CFR 1910.1200, they are not to be taken as a warranty or representation for which Performance Health, Inc. assumes legal responsibility. Performance Health, Inc. shall not be held liable or accountable for any loss or damage associated with the use of this material and information. The recommended industrial hygiene and safe use, handling, storage, and disposal procedures are believed to be generally applicable. However, since the use, handling, storage, and disposal are beyond Performance Health, Inc. control, it is the responsibility of the user both to determine safe conditions for use of this product and to assume liability of loss, damage, or expense arising out of the material's improper use.

#### HMIS Classification:

| Health Hazard:    | 1 |
|-------------------|---|
| Flammability:     | 2 |
| Physical Hazards: | 0 |

#### Legend:

ACGIH: American Conference of Governmental & Industrial Hygienists
CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL/NDSL: Domestic Substances List/Non-Domestic Substances List
EC Number: EINECS Number or ELINCS Number
EINECS: European Inventory of Existing Commercial Chemical Substance
ELINCS: European List of Notified Substances
EU: European Union
GHS: Globally Harmonized System of Chemical Classification and Labelling
HMIS: Hazardous Materials Identification System
IARC: International Agency for the Research of Cancer
IATA: International Air Traffic Association
ICAO: International Civil Aviation Organization

**IDLH:** Immediately Dangerous to Life or Health **IMDG:** International Maritime Dangerous Goods **IMO:** International Maritime Organizations MAK: Maximale Arbeitsplatzkonzentration (Exposure Limit) NIOSH: National Institute of Occupational Safety and Health NTP: National Toxicology Program NFPA: National Fire Protection Association NTP: National Toxicology Program **OSHA:** Occupational Safety & Health Administration PEL: Permissible Exposure Limits RCRA: Resource Conservation & Recovery Act **REL:** Recommended Exposure Limits RQ: Reportable Quantity RTK: Right-To-Know SARA: Superfund Amendments & Reauthorization Act **STEL:** Short Term Exposure Limit TLV: Threshold Limit Value **TSCA:** Toxic Substances Control Act **TWA:** Time Weighted Average TCLP: Toxicity Characteristic Leaching Procedure **US:** United States VOC: Volatile Organic Compounds