SAFETY DATA SHEET



Lysol Disinfectant Spray - 2 in 1 - Driftwood Waters

1. Product and company identification

: Lysol® Disinfectant Spray - 2 in 1 - Driftwood Waters **Product name**

: Reckitt Benckiser LLC. **Distributed by**

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Emergency telephone

number (Medical)

: 1-800-338-6167

Emergency telephone

number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: : http://www.rbnainfo.com

Product use : Disinfectant.

Consumer use

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of **USDOL** Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS# : D8339815 v2.0 : 3071515 v1.0 Formulation #: **EPA ID No.** : 777-99

UPC Code / Sizes : Aerosol Can

2. Hazards identification

Classification of the : FLAMMABLE AEROSOLS - Category 2

GASES UNDER PRESSURE - Compressed gas substance or mixture

EYE IRRITATION - Category 2B

GHS label elements

Hazard pictograms





Signal word : Warning

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 1/14

2. Hazards identification

Hazard statements

: Flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

Precautionary statements

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

Response

: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

: Not applicable.

Disposal Supplemental label

elements

: None known.

Hazards not otherwise classified

None known.

3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|-----------------|---------|------------|
| ethanol | 30 - 60 | 64-17-5 |
| butane | 5 - 10 | 106-97-8 |
| propane | 1 - 2.5 | 74-98-6 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 2/14

4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Moderately irritating to eyes.

Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. Skin contact Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data. Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 3/14

5. Fire-fighting measures

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Exposure limits

8. Exposure controls/personal protection

Control

Occupational exposure limits

Ingredient name

| Ingredient name | edient name Exposure limits | | | |
|-----------------|--|--|--|--|
| ethanol | ACGIH TLV (United States, 3/2015). | | | |
| | STEL: 1000 ppm 15 minutes. | | | |
| | OSHA PEL 1989 (United States, 3/1989). | | | |
| | TWA: 1000 ppm 8 hours. | | | |
| | TWA: 1900 mg/m ³ 8 hours. | | | |
| | NIOSH REL (United States, 10/2013). | | | |
| | TWA: 1000 ppm 10 hours. | | | |
| | TWA: 1900 mg/m³ 10 hours. | | | |
| | OSHA PEL (United States, 2/2013). | | | |
| | TWA: 1000 ppm 8 hours. | | | |
| | TWA: 1900 mg/m³ 8 hours. | | | |
| butane | OSHA PEL 1989 (United States, 3/1989). | | | |
| | TWA: 800 ppm 8 hours. | | | |
| | TWA: 1900 mg/m³ 8 hours. | | | |
| | NIOSH REL (United States, 10/2013). | | | |
| | TWA: 800 ppm 10 hours. | | | |
| | TWA: 1900 mg/m³ 10 hours. | | | |
| | ACGIH TLV (United States, 6/2013). | | | |
| | STEL: 1000 ppm 15 minutes. | | | |
| propane | OSHA PEL 1989 (United States, 3/1989). | | | |
| | TWA: 1000 ppm 8 hours. | | | |
| | TWA: 1800 mg/m³ 8 hours. | | | |
| | NIOSH REL (United States, 10/2013). | | | |
| | TWA: 1000 ppm 10 hours. | | | |
| | TWA: 1800 mg/m³ 10 hours. | | | |
| | OSHA PEL (United States, 2/2013). | | | |
| | TWA: 1000 ppm 8 hours. | | | |
| | TWA: 1800 mg/m ³ 8 hours. | | | |

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 5/14

8. Exposure controls/personal protection

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

9. Physical and chemical properties

Appearance

Physical state : Liquid. [Liquefied compressed gas.]

Color : Clear.

Odor threshold : Fragrant.

Not available.

pH : 10.5 to 11.8 [Conc. (% w/w): 100%]

Melting point : Not available.

Boiling point : Not available.

Flash point : Closed cup: 25.6°C (78.1°F)

9. Physical and chemical properties

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure: Not available.Vapor density: Not available.

Relative density : 0.85

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Aerosol product

Type of aerosol : Spray
Heat of combustion : 17.51 kJ/g
Ignition distance : <45.72 cm

10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials: Do not use with other products.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-----------------------|---------|--------------------------|----------|
| ethanol | LC50 Inhalation Vapor | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |
| butane | LC50 Inhalation Vapor | Rat | 658000 mg/m ³ | 4 hours |
| Lysol® Disinfectant Spray_FF3071515 (D8339815) | LC50 Inhalation Gas. | Rabbit | >2.75 mg/l | 4 hours |
| , | LD50 Dermal | Rat | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |

Conclusion/Summary

Not classified. Information is based on toxicity test result of the concentrate of a similar product.

Irritation/Corrosion

11. Toxicological information

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|---|---------|-------|---|-------------|
| ethanol | Eyes - Moderate irritant | Rabbit | - | 0.06666667 minutes 100 milligrams | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 100 microliters | - |
| | Eyes - Severe irritant | Rabbit | - | 500 milligrams | - |
| | Skin - Mild irritant | Rabbit | - | 400 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| Lysol® Disinfectant Spray_FF3071515 (D8339815) | Eyes - Mild irritant | Rabbit | - | 72 hours | 4 days |
| | Skin - Primary dermal irritation index (PDII) | Rabbit | 0.1 | 4 hours | 72 hours |

Conclusion/Summary

Skin

: Slightly irritating to the skin. * Information is based on toxicity test result of the concentrate of a similar product.

Eyes

: Moderately irritating to eyes. *Information is based on toxicity test result of the concentrate of a similar product.

Respiratory

: Based on available data, the classification criteria are not met.

Sensitization

| 3 | Route of exposure | Species | Result |
|--|-------------------|----------|-----------------|
| Lysol® Disinfectant Spray_FF3071515 (D8339815) | skin | In vitro | Not sensitizing |

Conclusion/Summary

Skin

: Non-sensitizer to skin. Information is based on toxicity test result of the concentrate of a similar product.

Respiratory

: Based on available data, the classification criteria are not met.

Mutagenicity

Not available.

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/Summary

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| ethanol | - | 1 | - |

Reproductive toxicity

Not available.

11. Toxicological information

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely :

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Moderately irritating to eyes.

Inhalation
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.

11. Toxicological information

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

12. Ecological information

Toxicity

| Result | Species | Exposure |
|--|--|--|
| Acute EC50 17.921 mg/l Marine water Acute EC50 2000 µg/l Fresh water Acute LC50 25500 µg/l Marine water Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 100 ul/L Fresh water | Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss Algae - Ulva pertusa Daphnia - Daphnia magna - | 96 hours 48 hours 48 hours 4 days 96 hours 21 days |
| | Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water Acute LC50 42000 μg/l Fresh water Chronic NOEC 4.995 mg/l Marine water | Acute EC50 17.921 mg/l Marine water Acute EC50 2000 µg/l Fresh water Acute LC50 25500 µg/l Marine water Acute LC50 42000 µg/l Fresh water Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Algae - Ulva pertusa Algae - Ulva pertusa Algae - Ulva pertusa Algae - Ulva pertusa |

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| ethanol | -0.35 | - | low |
| butane | 2.89 | - | low |
| propane | 1.09 | - | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|--------------------------|----------------|----------------------|----------------|-----|------------|------------------------|
| DOT Classification | UN1950 | Aerosols, flammable | 2.1 | III | \Diamond | Limited quantity |
| TDG Classification | UN1950 | Aerosols, flammable | 2.1 | III | \Diamond | Limited quantity |
| Mexico Classification | Not applicable | Not applicable | Not applicable | N/A | | Not applicable |
| IMDG Class | UN1950 | Aerosols, flammable | 2.1 | III | \Diamond | Limited quantity |
| IATA-DGR Class | UN1950 | Aerosols, flammable | 2.1 | III | *** | See DG List |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

PG*: Packing group

15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 311: ammonia

Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112 : Not listed (b) Hazardous Air **Pollutants (HAPs)**

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 11/14

15. Regulatory information

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312 Classification

: Fire hazard

Sudden release of pressure Immediate (acute) health hazard

Composition/information on ingredients

| Name | % | hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|---------|--------|--------|----------------------------------|----------|--|--|
| ethanol | 5 - 10 | Yes. | No. | No. | Yes. | No. |
| butane | | Yes. | Yes. | No. | No. | No. |
| propane | | Yes. | Yes. | No. | No. | No. |

State regulations

Massachusetts : The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL;

BUTANE: PROPANE

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE;

PROPANE

Pennsylvania : The following components are listed: DENATURED ALCOHOL; ETHANOL; BUTANE;

PROPANE

Canada

WHMIS (Canada) : Class B-2: Flammable liquid

Class B-5: Flammable aerosol.

Canadian lists

Canadian NPRI : The following components are listed: Ethanol; Butane (all isomers); Propane

CEPA Toxic substances : None of the components are listed.

: Not determined. Canada inventory

Label elements

Signal word: : CAUTION

Hazard statements : Causes moderate eye irritation

Precautionary measures

Code # : FF3071515 SDS# : D8339815 v2.0 **Date of issue** : 07/12/2018 12/14

15. Regulatory information

Do not spray in eyes, on skin or on clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

Keep out of reach of children.

Hazard statements



Flammable. CONTENTS UNDER PRESSURE.

Keep away from heat, sparks and open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.


Additional information : Store in original container in areas inaccessible to small children.

Do not reuse empty container. Do Not Puncture or Incinerate! (Replace cap and)

Discard in trash or offer for recycling if available.

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



NFPA (30B) aerosol Flammability Level 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Date of issue : 07/12/2018

Date of previous issue : 04/06/2018

Version : 2

Prepared by : Reckitt Benckiser India Ltd

Plot No 48 Sector - 32 Institutional Area Gurgaon, Haryana India - 122001

Revision comments : Update of the SDS

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.